



d5236



d5237

d5236
d5237



Item #	Lamping	Voltage	Shade Finish	Options	Sp. Orders
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

How to specify

d5236	-LED6	-120	-YL	<input type="text"/>	<input type="text"/>
-------	-------	------	-----	----------------------	----------------------

Work space for submittals

Example from illustration at left

Item Number d5236 BASIX 7 1/4" x 3 1/2" pendant
d5237 BASIX 7 1/4" x 8 1/4" pendant

Construction Aircraft cable supports fixture, height adjustable after installation.
Black, 3 conductor cord exits black, 5" diam. canopy.
For standard ceiling junction box mounting.
UL listed, cUL (ETL/ETLc for LED) certified for dry locations.

Lamping/Wattage
for d5236 **2C25** Incandescent, one 25 W, candelabra base, B-10 type LED,
LED8 8W LED with electronic driver. 736 Lumen output.t.
for d5237 **IN75** Incandescent, one 75 W, medium base, A type
LED8 LED, 8W LED with electronic driver. 736 Lumen output.

Voltage 120 120V 277 277V

Shade Finishes

AL Brushed Aluminum	G1 Light Grey	G2 Medium Grey
WH White Gloss	AN Metallic Anthracite	BG Black Gloss
MG Metallic Grey	BC Black Crinkle	C1 Metallic Copper
MB Matte Black	T1 Light Tan	T2 Medium Tan
BZ Metallic Bronze	SF Seafoam	BL Metallic Blue
GM Metallic Green	RB Bright Red	MP Magenta Pink
RD Metallic Red	OR Orange	
YL Bright Yellow	SCF Special Finish – must supply paint chip	

Options **COIL** Coiled electrical cord. **STEM** Rigid 1/2" diam. stem.
DIM Dimming Driver (0-10V, Triac, or ELV, as specified)

Special Orders For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.

