



d5401-LED12-120-AL

d5401/d5402



d5401-LED12-120-AL



Item #	Lamping	Voltage	Finish	Options	Sp. Orders
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Work space for submittals

How to specify

Example from illustration at left

d5401	-LED12	-120	-AL		
-------	--------	------	-----	--	--

Item Number **d5401** Coteau Pendant, 8" diameter
 d5402 Coteau Pendant, 9.5" diameter
 (with chrome lens ring and clamps, and flat acrylic lens)

Construction Spun aluminum or solid copper shade. Polished chrome trim, clamps and loop. White opal acrylic diffuser (d5402 only). 5" diam. black canopy. Adjustable height, aircraft cables support fixture. Black, 3 conductor cord. 60" overall height. For standard ceiling junction box mounting. UL listed, cUL (ETL/ETLc for LED) certified for dry locations.

Lamping / Wattage **LED12*** LED, 8W primary lamp source, with a 4W perforated decorative chamber
 1N100** Incandescent, one 100 W, medium base, A type.

* 3000K color temperature standard (also available in 2700K, 3500K, and 4000K)
 ** Medium base option excludes lamps. Lamps can be supplied by d'ac if requested"

Voltage 120 120V 277 277V

Finishes See Page d9000 & d9000 Supplement for color renderings

AL Brushed Aluminum	PA Polished Aluminum	Baked Enamels:
WH White Gloss	G1 Light Grey	G2 Medium Grey
MG Metallic Grey	AN Metallic Anthracite	BG Black Gloss
MB Matte Black	BC Black Crinkle	CU Metallic Copper
BZ Metallic Bronze	T1 Light Tan	T2 Medium Tan
GM Metallic Green	SF Seafoam	BL Metallic Blue
RD Metallic Red	RB Bright Red	MP Magenta Pink
YL Bright Yellow	SCF Special Finish—must supply paint chip	

Solid copper finishes:
CPL Polished Copper (lacquered) **CBL** Brushed Copper (lacquered)
CPU Polished Copper (unlacquered – will naturally tarnish over time)
CBU Brushed Copper (unlacquered – will naturally tarnish over time)

Options
DIM Dimming driver (must specify type: 0-10V, ELV, or Triac)
STEM Rigid, 1/2" diam. stem
COIL Coiled electrical cord.
TR Fixture can be modified for use with track systems. (adapter & track supplied by others)
INCP Inner shade in raw copper vs. painted white (standard on fixture) for copper finishes.
INCP2 Inner shade in copper paint vs. painted white (standard on fixture).
ISW Independent switching of accent light and downlight

Special Orders For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.