



# d5026P


## PERFEITO PENDANT

PROJECT:  
TYPE:  
QUANTITY:  
NOTES:


### SPECIFICATION

CONSTRUCTION	Spun-aluminum shade
ACCENTS	Perforated sleeve and brushed aluminum finial
CANOPY	5" diameter canopy
MOUNTING	Standard ceiling junction box
CORD	Black three-conductor cord
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
SHADE DIMENSION	18" diameter
OVERALL HEIGHT	60"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations

### DIMENSIONS



### RELATED PRODUCT: d5026



### ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5026P	<input type="checkbox"/> LED12 <sup>2</sup> 1200 TOTAL LUMENS, 80CRI <input type="checkbox"/> LED35 <sup>2</sup> 3500 TOTAL LUMENS, 90CRI <input type="checkbox"/> 1M60 <sup>4</sup> 60W MAX, MEDIUM BASE, A TYPE	<input type="checkbox"/> 120 <sup>1</sup> 120V <input type="checkbox"/> 277 277V	<input type="checkbox"/> AN METALLIC ANTHRACITE <input type="checkbox"/> BG BLACK GLOSS <input type="checkbox"/> BL METALLIC BLUE <input type="checkbox"/> BR BRIGHT RED <input type="checkbox"/> BZ METALLIC BRONZE <input type="checkbox"/> CU METALLIC COPPER <input type="checkbox"/> DR DAREDEVIL RED <input type="checkbox"/> FG FUSION GREEN <input type="checkbox"/> G1 LIGHT GRAY <input type="checkbox"/> GM METALLIC GREEN <input type="checkbox"/> MB MATTE BLACK <input type="checkbox"/> MG METALLIC GRAY	<input type="checkbox"/> WHC WHITE, THREE CONDUCTOR CORD <input type="checkbox"/> DIM <sup>3</sup> 0-10V DIMMING DRIVER <input type="checkbox"/> STEM <sup>5</sup> RIGID 1/2" DIAMETER STEM <input type="checkbox"/> EMP <sup>6</sup> EMERGENCY BATTERY PACK  <input type="checkbox"/> PBB PAINTED BRASS <input type="checkbox"/> PR MEDIUM BLUE <input type="checkbox"/> RD METALLIC RED <input type="checkbox"/> T2 MEDIUM TAN <input type="checkbox"/> WH WHITE GLOSS <input type="checkbox"/> YL BRIGHT YELLOW <input type="checkbox"/> SCF _____

### NOTES

1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED
2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K
3. 0-10V DIMMING DRIVER; COMPATIBLE WITH DEDICATED LED LAMPING. CONTACT FACTORY FOR ADDITIONAL DIMMING CONTROLS
4. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC
5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH
6. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY



Phone: 203.775.0172  
P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
dacLighting.com | cs@dacLighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice