



d85030


STADIO CEILING/WALL FIXTURE

PROJECT:
TYPE:
QUANTITY:
NOTES:

SPECIFICATION

CONSTRUCTION	Aluminum shade
DIFFUSER	White opal acrylic bottoms lens
ACCENTS	Polished chrome trim, clamps, and loops
MOUNTING	Standard ceiling junction box
FINISH	Metal or powder coat paint
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
DIMMING	0-10V dimming driver for dedicated LED
DIMENSIONS	13.8" diameter
DEPTH	15.5"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations

DIMENSIONS



RELATED PRODUCT: d5030



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
d5030C	LED12 ² 1200 TOTAL LUMENS, 90CRI LED35 ² 3500 TOTAL LUMENS, 90CRI 1M60 ⁴ 60W MAX, MEDIUM BASE, A TYPE	120 ¹ 120V 277 277V	AL BRUSHED ALUMINUM PA POLISHED ALUMINUM AN METALLIC ANTHRACITE BG BLACK GLOSS BL METALLIC BLUE BR BRIGHT RED BZ METALLIC BRONZE CU METALLIC COPPER DR DAREDEVIL RED FG FUSION GREEN G1 LIGHT GRAY GM METALLIC GREEN	EMP ⁵ EXTERNAL EMERGENCY BALLAST DIM ³ 0-10V DIMMING DRIVER MB MATTE BLACK MG METALLIC GRAY PBB PAINTED BRASS PR MEDIUM BLUE RD METALLIC RED WH WHITE GLOSS SCF

NOTES

1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED
2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K
3. 0-10V DIMMING DRIVER; COMPATIBLE WITH DEDICATED LED LAMPING. CONTACT FACTORY FOR ADDITIONAL DIMMING CONTROLS
4. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC
5. EXTERNAL EMERGENCY BALLAST MUST BE INSTALLED OUTSIDE OF THE FIXTURE ASSEMBLY AND BE WIRED TO THE LED DRIVER
6. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE



Phone: 203.775.0172
P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
dacLighting.com | cs@dacLighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice